

TECHNICAL DATA

TEHNIČNI PODATKI (Plastično togo jedro 0.5/5.5T)



DESCRIPTION / OPIS		
Total thickness / Skupna debelina	-	5.5 mm
Wear layer / Obrabni sloj	-	0.5 mm
Tile Size / Velikost plošč	-	177.8 x 1220 mm
Bevelled Edge / Pobrani robovi	-	Yes
Classification / Klasifikacija	EN ISO 10582	23: Domestic Heavy
	EN ISO 10582	32: Commercial General
	EN ISO 10582	41: Light industrial Moderate
Reaction to fire / Reakcija na ogenj	EN13501-1	B _{fl} – S1
	EN ISO 11925-2	Pass
	EN ISO 9239-1	Pass
	ASTM E 648-06	Class I
Resistance to Chemicals /Odpornost na kemikalije	EN 423	Class 0
	ASTM F 925	Pass
Resistance to Light /Odpornost na svetlobo	EN ISO 105-B02	≥6
	ASTM F 1515	< 8
Wear resistance /Odpornost proti obrabi	EN 660-2	Wear Group : P
	ASTM F 510	
Dimensional stability /Dimenzionalna stabilnost	EN 434	≤0.25%
	ASTM F 2199	Pass
Acoustic Impact / Zvočni učinek	EN ISO 717-2	ΔLw= 16 dB
Noise reduction / Zmanjšanje hrupa	EN ISO 140-8	
Static electrical propensity /Nagnjenost statične elektrike	EN 1815	Voltage: 0.5kV
Anti-slip property /Odpornost na zdrs	DIN 51130	R9
Castor chair continuous use /Stalna uporaba stola	ISO 4918	Pass

