



PROTECTILES+



Technical data	Standards	Protectiles+
Characteristics		
Description		Polypropylene textile pile on polyolefin under layer
Total thickness	EN 428 ISO 24346	5.2mm (± 0.4mm)
Total weight	EN 430 ISO 23997	3.060kg/m²
Technical performances		
Dimensional stability	EN 434	< 0.2%
Reaction to fire	EN 13501-1	B _{fl} s1 on cement
Acoustical absorption	EN 20354 ISO 354	(alpha) w=0.15 (H)
Impact sound reduction	ISO 140/8 NF EN ISO 717/2	L _w =19dB
Static electrical charge	EN 1815	< 2kV
Formaldehyde	EN 717-1 EN 727-2	No formaldehyde - E1
Pentachlorophenol	EN 12673	No pentachlorophenol
Underfloor heating compatibility	EN 12524	0.08 Ru=m² K/W Suitable - max 27°C

The above information is subject to modifications for the benefit of further improvement (12/2014).
For more detailed technical information, please contact Tarkett Sports



PROTECTILES+

Textile floor protection for social events

Main Product Features

- Effective solution to protect your floor from heavy weights and furniture (podium, stages etc.)
- Easy to install (less than 1.5 hour to install 1000m²) with dedicated Protectiles trolley (capacity 100 tiles)
- Easy to maintain

Logistics Information



Available in tiles 1 x 2m

General Information

